

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. **44 849 - 07 HH**

Company **Reichle & De-Massari AG**
Binzstrasse 31
8622 Wetzikon, SWITZERLAND

Product Description **Flexible use RJ45 connector with an 8-wire connection and Cat. 5e performance**

Type **FM45 connector 1 x RJ45/s/u Cat.5e, IP 20**
FM45 connector 1 x RJ45/s/u Cat.5e, IP67

Environmental Category **D**

Technical Data /
Range of Application **Pole count: 8**
Wire diameter section: Solid/wire 0,4 mm - 0,5 mm (AWG26-23)
Wire cross-section: Stranded/wire 0,12 mm² - 0,26 mm² (AWG 26/7 - 23/7)
Insulation material: Polycarbonate PC (UL-94-V0)
Contact durability: > 1000
Cable strain relief: > 50 N

Rated current: 1,75 A 20° C
Contact-resistance: < 1 mΩ (wire-IDC); < 5 mΩ (braid-IDC)
Plug contact: < 10 mΩ
Plug schieded: < 20 mΩ

Product code: R 312231 for FM45 connector 1xRJ45/s/u Cat.5e, IP 20
R 314686 for FM45 connector 1xRJ45/s/u Cat.5e, IP67

Test Standard **Guidelines for the Performance of Type Approvals Part 2, Edition 2003**
IEC 60603-7 RJ45 Cat. 5; IEC 60603-7-1 to 3:2002; EIA/TIA 568B:2002

Documents **Test report : TL020.291_a, dated 21.06.2007**
TL020291_c, dated 21.06.2007
TL020230, dated 22.07.2005

Remarks **None**

Valid until **2017-11-12**

Page **1 of 1**

File No. **I.N.02**

Hamburg, 2012-11-12

Type Approval Symbol



Germanischer Lloyd

W. Voß
Wolfgang Voß

C. Hunsalz
Carsten Hunsalz