

# PRIME Fiber Unit FTU BA HS for 48 SC/LCd/E2000/MPO



030.6164

## GENERAL DESCRIPTION

3 /4U PRIME FTU is the splice patch unit. The basic fiberinlay is suitable for 24/48 HS shrinkage contactors. Depending on the number of fibers, up to three additional MCM splice trays are equipped for 24/48 HS each. The fiber feed takes place via the back side. Suitable for PRIME-3U rack 19" Rack with front mounting.

PRODUCT-NO	PRODUCT DESCRIPTION
KPR-C8237810001	PRIME-Fiber Termination Unit (FTU), Back, Heatshrink splice protection, for 48, E-2000-Simplex/SC/Lcduplex/MPO, empty

## SCOPE OF SUPPLY

- 3/4U FTU-Unit unloaded
- 4 pcs. Cable ties, small
- 4 pcs. Plastic clip, small
- 1 pcs. Laser sign, small
- Installation manual

## MECHANICAL DATA

DESCRIPTION	VALUE / VALUERANGE
Color	metal sheet (Black-RAL 9005), front and fiber management (light gray-RAL 7035)
Material	metal sheet and plastic
Weight (Kg)	2.4

## CLIMATICAL DATA

DESCRIPTION	VALUE / VALUERANGE
Temperature range - in service	-25 °C to +70 °C / -13 °F to +158 °F
Temperature range - in storage & transport	-40 °C to +85 °C / -40 °F to +185 °F

## FIRE PROPERTIES

DESCRIPTION	VALUE / VALUERANGE
Halogen free, acid gases	Pass
RoHS	Pass

# PRIME Fiber Unit FTU BA HS for 48 SC/LCd/E2000/MPO

## TECHNICAL DRAWING

