

## PRIME – 1U Sub-Rack 19" front mount



### SCOPE OF SUPPLY

PRIME 1U Sub-Rack  
Mounting set  
Installation Guide

### GENERAL DESCRIPTION

The PRIME 1U-Sub-Rack empty includes sliders for a tool less installation for one PRIME-3/4U-Unit. The Sub-Rack is symmetrical and cable entry from the back is possible. The Sub-Rack is designed for all 19" Cabinets with a front mounting solution.

PRODUCT-NO	PRODUCT DESCRIPTION
R867703	PRIME-1U-Sub-rack-19"-FM, empty

### TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Mounting	19" front mount
Frame type	Slide-in unit
Fiber entry	Back (BA)

### MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Protection class IP	IP 20
Material	Metal
Color	RAL 7016 Anthracite gray
Weight [kgs]	2.7

## PRIME – 1U Sub-Rack 19" front mount

### CLIMATICAL DATA

DESCRIPTION		VALUE / VALUE RANGE
Temperature range	Service	-25 °C to +70 °C / -13 °F to +158 °F
	Storage	-40 °C to +85 °C / -40 °F to +185 °F
	Transport	-40 °C to +85 °C / -40 °F to +185 °F

### TECHNICAL DRAWING

